

SUPERTOP UPE LL

Suction and Delivery of Chemicals, Solvents and Food, PE-UHMV Tube



EN 12115:11 Tube: Reg. CE 1935/04 and CE 2023/06. Reg. EU 10/2011 aqueous and fatty foods. Phthalates free. PAHs free (acc. To ZEK 01.4-08 Cat 1) FDA tit. 21 item 177.1520 foods. BfR III.

Application: Hardwall hose suitable for handling a wide range of aggressive chemicals, solvents, alcohols and food. Normally installed on tank trucks and discharge platforms in chemical, oil and food industries. **Temperature:** From -40°C (-40°F) to +100°C (212°F)

Construction:

- **Tube:** White food quality smooth, high weight polyethylene (PE-UHMW). Chemical resistance according to IVG chemical resistance chart
- **Reinforcement:** High strength synthetic cord, steel helix wire and antistatic copper wire
- **Cover:** Green smooth (wrapped finish) EPDM rubber resistant to chemicals, abrasion, weathering and ozone
- **Electrical Resistance:** Type M electrical resistance guaranteed for lengths equal or lower than 40m

PART NUMBER	ID	ID	OD	OD	WORKING PRESSURE		BURST PRESSURE		WEIGHT NOMINAL		BEND RADIUS		VACUUM	LENGTH MAX	
	MM	INCH	MM	INCH	BAR	PSI	BAR	PSI	KG/M	LBS/FT	MM	INCH	BAR	MTR	FT
1399330	19	3/4	31	1.22	16	240	64	960	0.74	0.49	90	3.5	0.9	60	200
1399292	25	1	37	1.46	16	240	64	960	0.90	0.60	120	4.7	0.9	60	200
1399322	32	1 1/4	44	1.73	16	240	64	960	1.09	0.73	150	5.9	0.9	60	200
1399314	38	1 1/2	51	2.01	16	240	64	960	1.45	0.97	180	7.1	0.9	60	200
1399306	51	2	65	2.56	16	240	64	960	1.86	1.25	250	9.9	0.9	60	200
1407236	63.5	2 1/2	78	3.07	16	240	64	960	2.46	1.66	320	12.6	0.9	60	200
1399284	76	3	91	3.59	16	240	64	960	3.03	2.03	400	15.8	0.8	60	200
1400010	102	4	118	4.65	16	240	64	960	4.46	3.00	550	21.7	0.8	60	200