

Uni-Oil Standard Petroleum Service

Uni-OIL GG standard petroleum service hoses are designed for the transfer of a wide range of petroleum products. Uni-OIL GG hoses are ideal for transfer of media from storage tanks and process piping to rail cars or tank trucks.

Multiple plies of polypropylene films and fabrics are encased in a polyester vapour barrier for superior operation. Rated for full vacuum.

Uni-OIL GG

G-High Tensile Galvanised Carbon Steel Inner Helix
G-High Tensile Galvanised Carbon Steel Outer Helix

Manufactured in compliance with BS 5842. All Uni-CHEM® hose styles are constructed to marine specifications in accordance with US coast guard spec. 154.500 and IMO regulations. Available with EN 13765 compliant construction.



SIZE ID		MAX WORKING PRESSURE		BURST PRESSURE		BEND RADIUS		WEIGHT	MAX LENGTH
INS	MM	BAR	PSI	BAR	PSI	INS	MM	KG/M	MTR
1	25	14	200	56	800	4	104	0.89	40
1.5	38	14	200	56	800	5	130	1.19	40
2	50	14	200	56	800	6	155	2.40	40
2.5	63	14	200	56	800	7.9	203	2.53	40
3	75	14	200	56	800	8.1	208	3.60	40
4	100	14	200	56	800	11.9	355	4.77	40
6	152	14	200	56	800	22	560	10.73	30
8	203	14	200	56	800	30	760	16.39	24

Operating Temperature -40°C to +80°C. Standard colour: Black