

Uni-Zene Special Petroleum Service

Uni-ZENE special service petroleum hoses are designed to handle modern gasoline additives such as MTBE, ethanol and 31% benzene.

Uni-ZENE hoses are built with an effective combination of polyamide, polyester and polypropylene film and fabrics to meet the demands of today's additives. Also recommended for all JP aviation fuels. Rated for full vacuum.

Uni-ZENE

G-High Tensile Galvanised Carbon Steel Inner Helix

G-High Tensile Galvanised Carbon Steel Outer Helix



SIZE ID		MAX WORKING PRESSURE		BURST PRESSURE		BEND RADIUS		WEIGHT	MAX LENGTH
INS	MM	BAR	PSI	BAR	PSI	INS	MM	KG/M	MTR
1	25	14	200	56	800	4	104	0.89	40
1.5	38	14	200	56	800	5	130	1.19	40
2	50	14	200	56	800	6	155	2.40	40
2.5	63	14	200	56	800	7.9	203	2.53	40
3	75	14	200	56	800	8.1	208	3.60	40
4	100	14	200	56	800	11.9	355	4.77	40
6	152	14	200	56	800	22	560	10.73	30
8	203	14	200	56	800	30	760	16.39	24

Operating Temperature -40°F to +212°F / -40°C to +100°C. Standard colour: Red